

RANGE SUMMARY

The Genesis™ XE thin plate pure lead battery excels in demanding environmental and cycling applications such as:

- Alternative energy applications such as solar and wind power
- Hybrid electric vehicles (HEV)







Specifications

Battery Design

- 12V pure lead-tin VRLA AGM battery
- UL94 V-0 flame retardant case and cover
- M6 female no-maintenance terminals
- Can be installed in any orientation except inverted
- Rugged construction (optional metal jacket)
- Approved for shipping as non-hazardous, nonspillable

Performance Features

- -40°C to 80°C with metal jacket
- 300+ full depth of discharge cycles
- High rate charge and discharge
- 2 year shelf life at 25°C
- Superior deep discharge recovery
- UL listing - file No. MH12544
UL listing pending - XE60 and XE95



General specifications

Type	Nominal Voltage (V)	Nominal Capacity (Ah)	Nominal Dimensions			Overall Weight (kg)	Torque (Nm)	Internal Resistance (mΩ)	Typical Short Circuit Current (A)
		10 hr rate to 1.67Vpc @ 25°C	Length (mm)	Width (mm)	Height (mm)				
XE13	12	13	175.5	83.3	129.8	5.4	5.6	9.0	1400
XE16	12	16	181.6	76.2	167.9	6.4	5.6	7.5	1600
XE30	12	28	166.6	175.8	126.0	10.2	6.8	5.0	2400
XE40	12	42	197.1	165.9	170.7	16.1	6.8	4.5	2600
XE60	12	62	275.6	177.5	198.6	24.0	60	2.5	3100
XE70	12	68	330.7	168.1	176.0	25.7	60	3.5	3500
XE95	12	95	330.2	172.7	239.0	34.1	150	2.2	5000

Constant current discharge performance - amps to 1.67Vpc at 25°C

Battery	Minutes				Hours				
	5	10	15	30	1	5	8	10	20
XE13	68.8	42.4	31.4	18.2	10.2	2.5	1.6	1.3	0.7
XE16	81.4	51.4	38.4	22.4	12.6	3.0	2.0	1.6	0.9
XE30	131.4	84.4	63.5	37.6	21.5	5.2	3.4	2.9	1.5
XE40	196.3	125.6	94.3	55.7	31.6	7.7	5.0	4.2	2.2
XE60	304.4	193.6	144.4	84.2	47.2	11.4	7.5	6.2	3.4
XE70	334.1	215.1	169.0	95.8	54.3	12.9	8.3	6.8	3.5
XE95	449.5	290.7	219.5	129.5	73.5	17.8	11.7	9.6	5.2

Constant power discharge performance - watts per battery to 1.67Vpc at 25°C

Battery	Minutes				Hours				
	5	10	15	30	1	5	8	10	20
XE13	760.2	478.7	357.5	210.1	119.3	29.1	18.9	15.4	8.1
XE16	879.7	569.9	430.5	256.2	146.3	35.7	23.3	19.0	10.1
XE30	1447.7	951.4	723.5	435.0	250.6	62.5	41.1	33.6	18.2
XE40	2168.7	1420.6	1078.2	645.6	370.3	91.4	60.0	49.0	26.3
XE60	3337.2	2175.0	1644.0	976.2	556.2	136.8	90.0	73.8	40.2
XE70	3663.5	2422.4	1845.3	1107.9	633.9	152.0	98.1	79.5	41.4
XE95	4883.4	3241.8	2481.6	1494.0	861.6	212.4	139.8	114.0	61.2

Charge voltage

Cyclic use: 14.7V to 15.0V at 25°C. No current limit

Float use: 13.5V to 13.8V at 25°C. No current limit



EnerSys
P.O. Box 14145
Reading, PA 19612-4145
USA
Tel: +1-610-208-1991
+1-800-538-3627
Fax: +1-610-372-8613

EnerSys EMEA
Houtweg 26
1140 Brussels
Belgium
Tel: +32 (0)2 247 94 47
Fax: +32 (0)2 247 94 49

EnerSys Asia
49, Yanshan Road
Shekou, Shenzhen
Guangdong 518066
China
Tel: +86-755-2689 3639
Fax: +86-755-2689 8013

Contact:

© 2006 EnerSys. All rights reserved.
Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted.