

## THE FUEL CABINETS

EnerSys® Fuel Cabinets utilize either standard steel cylinders (6 or 9 each) or advanced composite fuel storage tanks (1-4 each). The Fuel Storage Modules feature welded aluminum, powder coated, weather tight construction and full width, swing open front doors.

The EnerSys advanced ultra high pressure (UHP) composite fuel tank solution provides more fuel storage capacity in the same space when compared to standard steel cylinders, and has the added capability of being refilled onsite. Their compact footprint and light weight make composite tanks ideal for small spaces or rooftop applications.



4-Bay Composite Tanks  
Fuel Storage Module  
(Model # 300)



9-Bay Steel Cylinders  
Fuel Storage Module  
(Model # 310)



2-Bay  
Composite Tanks  
Fuel Storage Module  
(Model # 320)

6-Bay  
Steel Cylinders  
Fuel Storage Module  
(Model # 330)



# FUEL CABINET SPECIFICATIONS

Steel Cylinders in Cabinet		6 Steel Cylinders - Model # 330	9 Steel Cylinders - Model # 310
<b>Physical</b>	Dimensions: (w x d x h)	25" x 41" x 72" / 64 cm x 104 cm x 183 cm	37" x 41" x 72" / 94 cm x 104 cm x 183 cm
	Set-Back Clearance Area: <sup>1</sup>	Contact customer service or AHJ <sup>1</sup>	Contact customer service or AHJ <sup>1</sup>
	Weight:	233 lbs / 106 kg (without cylinders)	309 lbs / 140 kg (without cylinders)
<b>Performance</b>	Storage Pressure:	2,200 psig / 155 kg/cm	2,200 psi / 155 kg/cm
	Capacity:	6.61 lbs / 3 kg	9.92 lbs / 4.5 kg
	Support:	40.6 kW - hr	61 kW - hr
	Support @ 5 kW:	8 hr	12 hr
<b>Operation</b>	Location:	Outdoor	Outdoor
	Fill Interface:	CGA-350	CGA-350

Composite Tanks in Cabinet		UHP - 2 (2 Tanks) - Model # 320	UHP - 4 (4 Tanks) - Model # 300
<b>Physical</b>	Dimensions (w x d x h):	25" x 41" x 72" / 64 cm x 104 cm x 183 cm	37" x 41" x 72" / 94 cm x 104 cm x 183 cm
	Set-Back Clearance Area: <sup>1</sup>	Contact customer service or AHJ <sup>1</sup>	Contact customer service or AHJ <sup>1</sup>
	Weight:	550 lbs / 250 kg (with cylinders)	880 / 400 kg (with cylinders)
<b>Performance</b>	Storage Pressure:	3,600 psig / 250 bar	3,600 psig / 250 bar
	Capacity:	11.6 lbs / 5.25 kg	23.15 lbs / 10.5 kg
	Support:	76 kW - hr	152 kW - hr
	Support @ 5 kW:	15 hr	30 hr
<b>Operation</b>	Location:	Outdoor	Outdoor
	Fill Interface:	SAE J2600 @ 250 bar	SAE J2600 @ 250 bar

1. Height clearance is in accordance with NFPA 55 and NFPA 853 based on siting location.

**NOTE:** Determine storage demand below and choose corresponding catalog number.

Estimated Runtime Hours						
kW Output	6 Steel Cylinders Model # 330	9 Steel Cylinders Model # 310	UHP - 1 (1 Tank) Model # 325	UHP - 2 (2 Tanks) Model # 320	UHP - 3 (3 Tanks) Model # 305	UHP - 4 (4 Tanks) Model # 300
5	8.5	12.8	7.5	15.0	22.5	30.0
10	4.3	6.4	3.8	7.5	11.3	15.0
15	2.8	4.3	2.5	5.0	7.5	10.0
20	2.1	3.2	1.9	3.8	5.6	7.5
30	1.4	2.1	1.3	2.5	3.8	5.0

Steel Cylinders based on 500 g (300 scf) per cylinder at 150 bar (2,200 psig)

Composite Tanks based on 2.62 kg (1108 scf) per tank at 250 bar (3,625 psig)

Based on 70 g per kW-hr

Only one fuel storage module per two engines maximum without additional options - due to flow capacity

Steel cylinder weight: 110 lbs / 50 kg each

Composite tank weight: 125 lbs / 57 kg each



www.enersys.com

**EnerSys**  
P.O. Box 14145  
Reading, PA 19612-4145  
USA  
Tel: +1-610-208-1991  
+1-800-538-3627  
Fax: +1-610-372-8613

**EnerSys EMEA**  
Brussels, Belgium  
Tel: +32 (0)2 247 94 47

**EnerSys Asia**  
Guangdong, China  
Tel: +86-755-2689 3639

Distributed by:

Printed in USA  
© 2009 EnerSys. All rights reserved.  
Trademarks and logos are the property of EnerSys and its affiliates, except Alteryx Freedom Power™, which is not the property of EnerSys.